

# FLEXFIT VERSTELBAARHEID

| GLASDIKTE 1.0 kN   | WINKEL | GLASHOOGTE 1000 mm | GLASHOOGTE 1100 mm | GLASHOOGTE 1200 mm |
|--------------------|--------|--------------------|--------------------|--------------------|
|                    |        | VERSTELBAARHEID    | VERSTELBAARHEID    | VERSTELBAARHEID    |
| 12 mm              | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 12,76 mm (6/6/2)   | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 13,52 mm (6/6/4)   | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 15 mm              | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 16,76 mm (8/8/2)   | 1,0°   | 28 mm              | 30 mm              | 34 mm              |
| 17,52 mm (8/8/4)   | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 19 mm              | 1,0°   | 18 mm              | 20 mm              | 22 mm              |
| 20,76 mm (10/10/2) | 1,0°   | 18 mm              | 20 mm              | 22 mm              |
| 21,52 mm (10/10/4) | 1,0°   | 18 mm              | 20 mm              | 22 mm              |

| GLASDIKTE 3.0 kN   | WINKEL | GLASHOOGTE 1000 mm | GLASHOOGTE 1100 mm | GLASHOOGTE 1200 mm |
|--------------------|--------|--------------------|--------------------|--------------------|
|                    |        | VERSTELBAARHEID    | VERSTELBAARHEID    | VERSTELBAARHEID    |
| 21,52 mm (10/10/4) | 1,0°   | 28 mm              | 30 mm              | 34 mm              |
| 25,52 mm (12/12/4) | 1,6°   | 28 mm              | 30 mm              | 34 mm              |
| 31,52 (15/15/4)    | 1,0°   | 18 mm              | 20 mm              | 22 mm              |

